

Compact Back-hoe Loaders (TLB's)

AMB50

Description

Introducing the Agrimech AMB50 Compact TLB - a compact powerhouse designed to redefine versatility and efficiency in construction. Engineered with recession and innovation, the AMB50 is your go-to solution for tackling a diverse range of tasks with ease.

Its robust build and advanced features ensure exceptional performance on various terrains. Whether it's excavation, loading, or landscaping, the Agrimech AMB50 Compact TLB stands ready to deliver reliability and productivity at every turn.



Specs		HD50
General	Length x Width x Height	6,000 x 1,850 x 2,800mm
	Operating Weight	5,000kg
	Maximum Speed	28km/h
	Maximum Grade ability Capacity	25°
	Wheel Base	2,050mm
	Track	1,530mm
	Min. Ground Clearance	260mm
Loader	Loading Bucket Capacity	0.8m ³
	Rated Loading Capacity	1,600kg
	Maximum Lift Height	3,700mm
	Bucket Dumping Height	2,700mm
	Dumping Distance	1,000mm
Backhoe	Backhoe Bucket Capacity	0.2m ³
	Maximum Digging Depth	3,400mm
	Maximum Digging Height	5,000mm
	Maximum Digging Radius	4,600mm
	Boom Slewing Angle	190°
Engine & Transmission	Model	XINCHAI A498BT1
	Engine Power	36.8kW (49.4HP)
	Hydraulic Pump	Fixed shaft power shift transmission
	Gear Shift	2 forward shift 2 reverse shift
Tyres and brakes	Tyre	23.5/70-16
	Service Braking	Air brakes
	Parking Brake	Manual parking brake

