750L Twin Shaft Mixer

RTM-750



Revaro manufactures twin-shaft forced mixers equipped with lifting Hoist. It produces 0.5 to 2 cubic metres of concrete per batch. The mixer is suitable to mix dry concrete, plastic concrete, fluid concrete, lightweight aggregate concrete and wet mortar.

This series of twin-shaft concrete mixers are characterized by energy saving, environmental protection, stable operation and long service life. In addition, the hopper type twin shaft mixers can be used as a simple concrete batching plant to produce ready-mixed concrete, precast concrete and so on.

- **Long Life:**? Featuring wear-resistant, replaceable liners, and boasts hardened MN steel, capable of doing up to 100 000 mixes.
- **More Effective:**? The twin-shaft arm configuration is designed to speed up mixing times, saving you money.
- **Economical:**? Efficient mixing and time saving saves you on electricity, manpower and money.
- **Discharge height:**? As required on a platform to supply aggregate to conveyors through specialized chutes?

Specs

Machine Specs	
Discharge Capacity	750L
Feeding Capacity	1200L
Theoretic Production	35m3/h
Aggregate Diametre	40 / 60mm
Cycle Time	72s
Weight	5500kg
Dimensions	
Transportation	3 110 x 2 620 x 2 580mm
Working	5 025 x 3 100 x 5 680mm
Mixing Blade	
Speed	31rpm
Quantity	2 x 7
Mixing Motor	
Model	Y200-4

Power	30kW
Hoisting Motor	
Model	YEZ132m-4
Power	7.5kW
Water Pump Motor	
Model	BL12-16-1.1
Power	1.1kW