



500L Twin Shaft Mixer with skip

RTM-500

Revaro manufactures twin-shaft forced mixers equipped with lifting Hoist. It produces 0.5 to 2 cubic metres of concrete per batch. The mixer is suitable to mix dry concrete, plastic concrete, fluid concrete, lightweight aggregate concrete and wet mortar.

This series of twin-shaft concrete mixers are characterized by energy saving, environmental protection, stable operation and long service life. In addition, the hopper type twin shaft mixers can be used as a simple concrete batching plant to produce ready-mixed concrete, precast concrete and so on.

- **Long Life:** Featuring wear-resistant, replaceable liners, and boasts hardened MN steel, capable of doing up to 100 000 mixes.
- **More Effective:** The twin-shaft arm configuration is designed to speed up mixing times, saving you money.
- **Economical:** Efficient mixing and time saving saves you on electricity, manpower and money.
- **Discharge height:** As required on a platform to supply aggregate to conveyors through specialized chutes?



Specs

Machine Specs	
Discharge Capacity	500L
Feeding Capacity	800L
Theoretic Production	25m ³ /h
Aggregate Diametre	40 / 50mm
Cycle Time	72s
Weight	4000kg
Skip	Included
Dimensions	
Transportation	3 050 x 2 530 x 2 680mm
Working	4 460 x 3 050 x 2 680mm
Mixing Blade	
Speed	31rpm
Quantity	2 x 7
Mixing Motor	





Model	180m-4
Power	18.5kW
Hoisting Motor	
Model	YEZ132m-4
Power	5.5kW
Water Pump Motor	
Model	BL12-16-1.1
Power	1.1kW

