



1500L Twin-Shaft Mixer

RTM-1500

Revaro manufactures twin-shaft forced mixers equipped with lifting Hoist. It produces 0.5 to 2 cubic metres of concrete per batch. The mixer is suitable to mix dry concrete, plastic concrete, fluid concrete, lightweight aggregate concrete and wet mortar.

This series of twin-shaft concrete mixers are characterized by energy saving, environmental protection, stable operation and long service life. In addition, the hopper type twin shaft mixers can be used as a simple concrete batching plant to produce ready-mixed concrete, precast concrete and so on.

- **Long Life:** Featuring wear-resistant, replaceable liners, and boasts hardened MN steel, capable of doing up to 100 000 mixes.
- **More Effective:** The twin-shaft arm configuration is designed to speed up mixing times, saving you money.
- **Economical:** Efficient mixing and time saving saves you on electricity, manpower and money.
- **Discharge height:** As required on a platform to supply aggregate to conveyors through specialized chutes



Specs

Machine Specs	
Discharge Capacity	1500L
Feeding Capacity	2400L
Theoretic Production	75m ³ /h
Aggregate Diametre	80/60mm
Cycle Time	60s
Weight	11130kg
Dimensions	
Transportation	5 058 x 2 250 x 2 440mm
Working	9 645 x 3 436 x 9 700mm
Mixing Blade	
Speed	25.5rpm
Quantity	2 x 8
Mixing Motor	
Model	Y180-4





Power	2x 44kW
Hoisting Motor	
Model	YEZ160m-4
Power	22kW
Water Pump Motor	
Model	BOJDB-45
Power	3kW

